




Geant4 liquid Argon Validation



Outline




Validation of LAr TPC physics

Hadronic Cross Sections

Electromagnetic showers

Muon separation



Simulation of Liquid Argon TPC

Introduction

Step Limiter

Divided Steps

Segmented Geometry



Introduction




The scope of this project was to look into various physics processes relevant to Liquid Argon TPC detector response.

In addition, we were interested in the details of LArSoft simulation and to explore alternative methods to implement the simulation.



Hadronic XS





$$XS = \frac{N_{interacted}}{N_{total}} \cdot \frac{A}{N_a \cdot d \cdot T}$$

Hadronic XS

Thanks to Rasheed

Auguste for


- Pions, Kaons, Nucleons
- Cross Sections in Liquid Argon, no experimental data
- Comparison with experimental data in Carbon and other materials

- **Geant4**: → https://github.com/hanswenzel/G4HadStudies

 Start Event. Use Sensitive Detector (Stepping Action) to detect interactions: Elastic interaction might not put new particle on the Stack (UserStackingAction)


- If Inelastic or elastic interaction, increment
- Calculate XS from number that interacted


We know what to expect: The cross section scales linearly with A^(2/3)



Pion **Cross Section**

- Matches well with experimental data






Isaac Harris 6

1600 1800 2000

Kaon **Cross Section**

- Matches poorly with



A: 40

2000

1800

1600

1400

1200

1000

800

Fotal XS [mb]

Isaac Harris

Liquid Argon

Physics List: QGSP_BERT

Geant 4.10.1.po2

Statistical Errors only

- K Total XS K* Total XS

K Inelastic XS

K* Inelastic XS

Elastic XS


K* Elastic XS


A: 40 Liquid Argon

华

Nucleon Cross Section

- Matches well with experimental data









Transverse Shower Profile

IAr: Radial Energy Profile

- Sensitive Detector: Stepping Action
- Collect energy deposited from shower run
- Integrate histogram until at 90% of total integral
- Molière Radius always comes out high compared to literature values
- This has been brought up before
- $dE/dX = a\mathbf{e}^{-r/R_m} + b\mathbf{e}^{-r/\lambda_{min}}$





Simulated Literature [cm]

Pb: 1.95 1.6 Fe: 2.79 1.72

IAr: 14.34 10.1

Muon +/- Separation (50MeV)



Processes	μ-	μ+
Decay* Lifetime Probability	e-, ν _e , ν _μ .58μs 25%	e+, ν _e , ν _μ 2.2μs 100%
Capture Probability	ν _μ , γ ** 75%	none


**there can be more than one \mathbf{y} emitted in nuclear capture

Stacking Action: look at particles, processes, energies, and timing when new particles are put on the stack

^{*} for μ -, it is Decay in Orbit

Muon Decay






The values for the lifetimes of the muons are consistent with findings from previous experiments. Suzuki et al measured mu- lifetime in liquid Argon, and it is ~.58 µs





- Radiative, gammas produced
- Low energy gammas from atomic capture produces spectrum





Part II: LAr TPC Simulation

Liquid Argon Specifics



- Steps must be matched to readout pitch
- Scintillation and Ionization compete
- dE/dX = 2.1 MeV/cm
- Ionizing: 23.6 eV per electron pair


(Ereditato)

Scintillation: 19.5 eV




Detector simulation





Matching Step Length and Readout Pitch






All energy deposited here

Geant4 adjusts the step size according to the physics, and for some processes, the step size is much greater than the readout pitch.


For energy deposits, we expect landau distributions with a most probable value at 2.1 MeV/cm (muon approximates minimum ionizing particle)


Solutions





Step Limiter







Segmented Geometry


Step Limiter

- + Very Simple to implement
- + No added memory costs
- + Gets physics right when Step limiter is about one tenth of the wire pitch
- Takes a long time for small step sizes (> .72 sec/event, .1 mm)





Energies (1mm stepMax), 12mm



Step Limiter



In DetectorConstruction.cc:

```
G4UserLimits *fStepLimit = new G4UserLimits(maxStepSize);
DetectorLogicalVolume -> SetUserLimits(fStepLimit);
```

• In g4main.cc:


```
phys->RegisterPhysics(new G4StepLimiterPhysics());

G4VModularPhysicsList
```


Divided Steps


+ Takes little time even for many Divisions (< .06 sec/event)

 Huge memory costs for many pixels



- Never gets the physics right







Segmented Geometry (Voxels)



- + Gets physics right when readout matches division size, otherwise acts as step limiter
- Deals with many volumes Ex: 1m TPC & .3 mm cubes = **37,000,000,000** volumes
- Takes a long time for small voxel sizes (>.9 sec/event, .1 mm)
- Cannot match wires exactly to voxels (stereo readout)






Very little added memory costs (10MB)






Computing Time




Segmented Geometry (Voxels)



- + Gets physics right when readout matches division size, otherwise acts as step limiter
- Deals with many volumes Ex: 1m TPC & .3 mm cubes = **37,000,000,000** volumes
- Takes a long time for small voxel sizes (>2.5 hrs for 10,000 muons, .1 mm)
- Cannot match wires exactly to voxels (stereo readout)





Very little added memory costs (10MB)

Conclusion



- In general, there was good agreement between Geant4 simulation and experimental data
- The Moliere Radius Studies aren't conclusive, studies need follow-up
- Evaluated three ways to match the step length to the wire pitch, and the step limiter is a good alternative to the segmented geometry which is currently in LarSoft/LArG4

Thank You!

- Hans Wenzel
- Metcalf Program
- Fermilab PDS group
- LArIAT

